


ORDER CODE

Displacement transducer

PK



4-pole connector output DIN43650-ISO4400	M
5-pole connector output DIN43322	B

No certificate attached	0
Linearity curve to be attached	L

Model

Color of plastic heads (green)	0
-----------------------------------	----------

Example: **PK - M - 0300 000X000X00**

PK displacement transducer, 4-pole connector output DIN43650 - ISO 4400, useful electrical stroke (C.E.U.) 300mm., no certificate attached; green plastic components

ACCESSORIES (standard)

Fixing kit for PK from 100 to 900: 2 brackets, screws, grower

PKIT 059

Fixing kit for PK from 1000 to 2000: 3 brackets, screws, grower

PKIT 061

ACCESSORIES (optional)

PKM 4-pole 90° radial female connector DIN43650; IP65 PG9 clamp for ø 6-8 mm. cable

CON006

PKB 5-pole axial female connector DIN43322; IP40 clamp for ø 4-6 mm. cable

CON011

PKB 5-pole axial female connector DIN43322; IP65 PG7 clamp for ø 4-6 mm. cable

CON012

PKB 5-pole 90° radial female connector DIN43322; IP40 clamp for ø 4-6 mm cable

CON013

GEFRAN spa reserves the right to make any kind of design or functional modification at any moment without prior notice